



FX20
Optical Power Meter

## **Key Features**

- High accuracy and wide dynamic range (up to 26 dBM with H option)
- 1000 test results storage
- Test results transfer to PC via USB connection
- Intelligent backlight
- Reference power level setup and recall
- User self-calibration
- · Auto power off

## **Specifications**

- Calibration wavelength: 800 nm to 1700 nm
- Detector type: InGaAs
- Measurement range: -70 to +10 dBm or-50 to +26 dBm (H option)
- Accuracy: +0.2 dB or 5% whichever larger
- Linearity: 0.01 dB
- Display resolution: 0.03 dB
- Frequency ID: 270, 330, 1K, 2K Hz
- Wave ID: 850, 980, 1300, 1310, 1490, 1550, 1625 nm
- Test results storage: 1000Communication port: USB
- Connector: FC/SC/ST Interchangeable
- Battery: 3 Alkaline AA
- Battery operating time: 240 hour without backlight
- Operation temperature: -10°C to +60°C
   Storage temperature: -25°C to +70°C
   Dimension: 172 mm x 82 mm x 33 mm
- Weight: 310 g (0.7 lb)



VeEX Inc. 2827 Lakeview Court Fremont, CA 94538 USA Tel: +1.510.651.0500 Fax: +1.510.651.0505 www.veexinc.com customercare@veexinc.com

VeEX is a registered trademark of VeEX Inc. The information contained in this document is accurate. However, we reserve the right to change any contents at any time without notice. We accept no responsibility for any errors or omissions. In case of discrepancy, the web version takes precedence over any printed literature.

D05-00-084P A00 2014/08